

Threaded

97/23/EC Directive N°0035 - Risk category III / module H - CF8M body - F304 screen - Mesh 1 mm - With draining cap - PS: 16 bar - TS: -20°C/+200°C.




230 - Stainless steel (BSP)

Ø	1/4"	3/8"	1/2"	3/4"	1"	1"1/4"	1"1/2"	2"
code	230002	230003	230004	230005	230006	230007	230008	230009

Flanged

Excluded from 97/23/EC Directive (article 1, §3.2) - Flanged RF PN10/16 up to DN150, PN10 or PN16 above - EN 558 series 1 - GG25 body - Stainless steel screen - With draining cap - PS: 10 bar for PN10 strainers, 16 bar for PN16 strainers.



220 - Cast iron

F304 screen - Grey epoxy paint - TS: -10°C/+120°C.

DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400
mesh (mm)	1,1	1,1	1,1	1,1	1,1	1,1	1,1	1,1	1,1	1,1	1,5	1,5	1,5	1,5	3	3
face to face	130	150	160	180	200	230	290	310	350	400	480	600	730	850	980	1100
PN10 code	-	-	-	-	-	-	-	-	-	-	-	220201	220250	220300	220350	220400
PN16 code	220015	220020	220025	220032	220040	220050	220065	220080	220100	220125	220150	220200	220251	220301	-	-

233 - Cast iron - Water use

F316 screen & draining cap - Blue epoxy paint - TS: -10°C/+80°C.



DN	40	50	65	80	100	125	150	200/10	200/16	250/10	250/16	300/10	300/16
mesh (mm)	1	1	1,25	1,25	1,6	1,6	1,6	1,6	1,6	1,6	1,6	1,6	1,6
face to face	200	230	290	310	350	400	480	600	600	730	730	850	850
code	233040	233050	233065	233080	233100	233125	233150	233200	233201	233250	233251	233300	233301

97/23/EC Directive N°0062 - Risk category III / module H - Flanged PN16 - DIN 3202 F1 - GG25 body - F304 screen - With draining cap - PS: 16 bar - TS: -10°C/+300°C - ⚠️ **Steam up to 10 bar max.**



236 - Cast iron - High temperature



DN	15	20	25	32	40	50	65	80	100	125	150	200
mesh (mm)	1	1	1	1	1	1	1,25	1,25	1,6	1,6	1,6	1,6
face to face	130	150	160	180	200	230	290	310	350	400	480	600
code	236015	236020	236025	236032	236040	236050	236065	236080	236100	236125	236150	236200

97/23/EC Directive N°0062 - Risk category III / module H - Flanged RF PN40 - EN 558 series 1 - A216WCB body - F304 screen - PS: 40 bar - TS: -20°C/+425°C.




235 - Carbon steel - High temperature



DN	15	20	25	32	40	50	65	80	100	125	150	200
mesh (mm)	1	1	1	1	1	1	1,25	1,25	1,6	1,6	1,6	1,6
face to face	130	150	160	180	200	230	290	310	350	400	480	600
code	235015	235020	235025	235032	235040	235050	235065	235080	235100	235125	235150	235200

97/23/EC Directive N°0035 - Risk category III / module H - Flanged RF PN16 - EN 558 series 1 - CF8M body - F304 screen - PS: 16 bar - TS: -20°C/+200°C.



240 - Stainless steel

DN	15	20	25	32	40	50	65	80	100	125	150	200
mesh (mm)	0,8	0,8	0,8	0,8	0,8	0,8	1	1	3	3	3	3
face to face	130	150	160	180	200	230	290	310	350	400	480	600
code	240015	240020	240025	240032	240040	240050	240065	240080	240100	240125	240150	240200

